

Environmental Product Declaration



In accordance with ISO 14025:2006 and EN 15804:2012+A2:2019/AC:2021 for:

Grip Coat, granulated No. 506

from

AURO Pflanzenchemie AG



Programme:

Programme operator:

EPD registration number:

Publication date:

Valid until:

The International EPD® System, www.environdec.com

EPD International AB

EPD-IES-0023238:001

2025-06-20

2030-06-20

An EPD should provide current information and may be updated if conditions change. The stated validity is therefore subject to the continued registration and publication at www.environdec.com



General information

Programme information

Programme:	The International EPD® System
Address:	EPD International AB Box 210 60 SE-100 31 Stockholm Sweden
Website:	www.environdec.com
E-mail:	info@environdec.com

Accountabilities for PCR, LCA and independent, third-party verification
Product Category Rules (PCR)
CEN standard EN 15804 serves as the Core Product Category Rules (PCR)
Product Category Rules (PCR): Construction Products, PCR 2019:14, version 1.3.4
PCR review was conducted by: The Technical Committee of the International EPD System. See www.environdec.com for a list of members. Review chair: Claudia A. Peña, University of Concepción, Chile. The review panel may be contacted via the Secretariat www.environdec.com/contact .
Life Cycle Assessment (LCA)
LCA accountability: Dr. Christopher Hirth, AURO Pflanzenchemie AG
Third-party verification
Independent third-party verification of the declaration and data, according to ISO 14025:2006, via: ☒ EPD verification by individual verifier Third-party verifier: Andreas Ciroth, GreenDelta GmbH Approved by: The International EPD® System
Procedure for follow-up of data during EPD validity involves third party verifier: ☐ Yes ☒ No

The EPD owner has the sole ownership, liability, and responsibility for the EPD.

EPDs within the same product category but registered in different EPD programmes, or not compliant with EN 15804, may not be comparable. For two EPDs to be comparable, they must be based on the same PCR (including the same version number) or be based on fully-aligned PCRs or versions of PCRs; cover products with identical functions, technical performances and use (e.g. identical declared/functional units); have equivalent system boundaries and descriptions of data; apply equivalent data quality requirements, methods of data collection, and allocation methods; apply identical cut-off rules and impact assessment methods (including the same version of characterisation factors); have equivalent content declarations; and be valid at the time of comparison. For further information about comparability, see EN 15804 and ISO 14025.

Company information

Owner of the EPD and location of production site:

AURO Pflanzenchemie AG, Alte Frankfurter Str. 211 A, 38122 Braunschweig, Germany

Contact:

Dr. Christopher Hirth | R&D Chemist | info@auro.de

Description of the organisation:

AURO has been an undisputed pioneer in the field of ecological natural paints for over 40 years, specializing in products for home and garden. Our products are created from a clear vision: a "green chemistry" based on sustainable, plant-based, and mineral raw materials, avoiding petroleum. This philosophy was initiated by our founder, chemist Dr. Hermann Fischer, and continues to shape our work to this day.



Sustainability is a core element of our company philosophy, which has remained unchanged since our founding in 1983. We focus on a future-proof, nature-friendly economy and actively engage in climate protection. Our products are not only environmentally conscious but also technically advanced and highly efficient. They theoretically can be easily returned to the natural cycle, thus actively contributing to environmental protection.



Since our founding, AURO has represented a vision: to develop paints and coatings that not only offer the highest quality but also respect both people and nature. As pioneers of "green chemistry," we consistently rely on plant-based and mineral raw materials. Our goal is to create long-lasting alternatives that harmonize living health, environmental compatibility, and aesthetic beauty.

For us, sustainability means more than just biological ingredients. We pursue a holistic approach: from responsible raw material sourcing to resource-efficient production and

biodegradable end products. Our processes are low in CO₂, we aim to make our packaging as environmentally friendly as possible, and all our actions are geared towards preserving nature.

Thanks to decades of research, we have developed a unique product range that sets standards in eco-consciousness, functionality, and durability. Whether wall paints, wood stains, or varnishes – our new formulations are emission-free and promote a healthy indoor climate.

AURO's ecological natural paints are distinguished by their unique radiance. They offer harmonious colour effects, high colour fastness, and an authentic, natural appearance – always in harmony with the biological raw materials they contain. With a perfect combination of quality and ecological commitment, we are now the market leader in the field of natural paints and are represented in numerous countries worldwide.



But AURO is more than just a paint manufacturer: We share our knowledge, promote education, and drive innovation in the earth-friendly building and living industry. Through expert articles, books, and research, we are making true pioneering contributions for a future in which healthy living and environmental protection are a matter of course.

We maintain long-term, cooperative relationships with our suppliers and customers and treat both them and our employees with respect and appreciation. We promote fair partnerships, particularly in the growing areas of the exotic raw materials we use.

Product-related or management system-related certifications:



Product information

Product name:

Grip Coat, granulated No. 506

Product identification:

Products in the AURO portfolio are identified by their characteristic name and number.

Product description:

The problem solver for all difficult substrates: Preservative-free primer with grit for better adhesion of subsequent coats for interior and exterior use.

- Application with roller or brush
- Open to diffusion/breathable
- Emission-free
- Odourless primer
- Low-drip and low-splash application
- Can be painted over with all AURO wall paints and plasters
- Can be recoated after 4-6 hours
- Professional product properties guaranteed by biogenic binder REPLEBIN[®]

Apply two coats outdoors, then the grip coat can be painted over with AURO High-grade lime paint No. 344.

Dangerous substances from the candidate list of SVHC:

The declared product in this EPD[®] does not contain any of the "substances of very high concern for authorisation" (SVHC) according to article 59 (10) of the REACH Regulation (last accessed 08.04.2025).

UN CPC code:

3511 Paints and varnishes and related products

Geographical scope:

GLO/RER/GER

While AURO focusses on sustainable and ecologic raw materials, some of the natural, partly exotic substances have their sources overseas and therefore a global (GLO) scope. Most materials are sourced locally in Germany (GER) or Europe (RER). Production is centred in Braunschweig, Germany. The assumed scenarios for application, use and end-of-life are based on European standards.

LCA information

Declared unit:

The declared unit is 1 m² of surface covered by the indicated product and consists of the necessary amount of raw materials, transportation, manufacturing, waste treatment and their corresponding environmental impacts related to the specific product. A weight-based approach was used for averaging products, predominantly the tintable paints of the COLOURS FOR LIFE series. The conversion rates of the product consumption for coating the declared area are 0.13 kg/m² or 0.08 L/m².

Reference service life:

10 years

Time representativeness:

2023

Database(s) and LCA software used:

ecoinvent v.3.10 and Circonomit LCA tool v.1.0

Description of system boundaries:

The chosen EPD® type for construction products according to EN 15804 and the PCR 2019:14, version 1.3.4 is "Cradle to gate with modules C1–C4 and module D (A1–A3 + C + D)". The reasoning for this choice of declaration and omissions, as well as the assumptions made for each module are explained here after.

As stated in the PCR, the characterization factors are based on the EF 3.1 version of the EN15804 reference package.

System diagram:



* D – Reuse, recovery, recycling, potential: While it is theoretically possible to decompose ecological wall paints, it is, at this point in time, highly impractical, uneconomic and unusual to separate them from their substrate for a dedicated recycling effort to achieve a full cradle-to-cradle life cycle.

Detailed description of modules, assumed scenarios and additional information

A1-A3 Production stage

The production stage includes the supply of raw materials (A1), the transport of raw materials to the manufacturer (A2) and the manufacturing process itself at the production site (A3).

As module A1 includes all relevant resources committed to the extraction and processing of the materials, it is generally speaking the most impactful module for wall paint products.

Module A2 describes the transportation of raw materials to the production site and therefore consists mostly of the concrete transport distance between the distributor or producer of a given material and the manufacturer, modelled with a dataset for the most often used truck category in this context. The

average transportation scenario for AURO assumes freight lorries with a capacity of 16-32 metric ton, EURO6 in a European setting (RER).

Module A3 encompasses the manufacturing process at AURO. The steps reach from material processing, which is key for the production of the self-developed and proprietary REPLEBIN® binder, over paint production by mixing the components batchwise according to the recipe with a dissolver and filling the products into adequate containers to packaging them ready for transport to customers (A4), as shown in Figure 1 General Production Process:




Figure 1 General Production Process

Internal transportation in the facility exclusively by electric forklifts and pallet trucks is also taken into account.

Not accounted were production and maintenance of machinery and vehicles on site (including wooden multi-use pallets), other maintenance work regarding the production plant, the employees' daily commute and research and development and sales activities on site.

Not all suppliers for biobased materials used at AURO have primary data for LCA studies available yet. Especially the materials for REPLEBIN®, PCR plastics and their respective environmental impacts and are difficult to estimate. Therefore, some (if necessary even petrochemical) alternatives were used as proxies for the LCA calculations, serving as a conservative estimate of AURO's ecological dedication.

The electricity mix used at AURO is 100% renewable and reported with both 0 g carbon dioxide emissions and radioactive waste per kWh according to the supplier.¹ It was modelled with a data set for renewable energy products that still has minor carbon dioxide emissions and radioactive waste remaining, again serving as a conservative estimate of AURO's ecological commitment.

¹ Scholt Energy – Green Electricity 'Garantiert Grün'. For more information, please follow the link provided in the References section.

A4-A5 Construction process stage

The construction process stage handles the transport of products from the manufacturer to distributors, retailers and end-customers (A4) and subsequently the installation of the product for its intended use (A5), mainly by brush or roller application. As AURO distributes its products globally, but with a majority of European customers, it is challenging to average a representative transport distance from AURO to the end-customer and deducing the correct composition of the applied means of transportation. Especially the certain share of DIY customers buying locally from AURO's retailer network is a great unknown for approximation.

With such an uncertainty in calculated average values and possibly enormous deviations from these values in single cases, representativeness is not a given and the module is therefore not declared. It is estimated to be the second most impactful segment of the whole life cycle, after the combination of modules A1-A3.

Regarding the installation process, the product is attuned to being immediately applicable by brush or roller, in some cases also by spraying. Without the need for extra dilution with water (though possible) or energy intake, leaving only the waste treatment of packaging material and paint residue, the total impact of this module is estimated to be very low. So, while a basic model for the installation process is feasible, it is ill-advised to only declare this part of the construction stage and it is therefore also omitted. As a consequence, the results of A1-A3 already include the "balancing-out-reporting" of the biogenic CO₂ of packaging released in module A5.

B1-B7 Use stage

The use stage includes all environmental impacts caused by the product during its reference life time of approximately 10 years, for example by reactions with the ambient surrounding in form of emissions or material uptake, necessary maintenance or repair. None of these apply for the emission-free wall paint products. Thus, the module is not declared.

C1-C4 End-of-life stage

The end-of-life stage is dedicated to the appropriate disposal of the product after its reference life time and all steps necessary to do so.

As the wall paint product is usually not separated from its substrate before deconstruction and demolition (C1) and instead treated as part of the wall material, no impacts are declared for module C1. Instead, the typical disposal scenario for bricks and concrete is applied: Transport of the debris to a landfill (C2) and ensuing disposal (C4) without the need for waste processing (C3).

For a typical European or German landfill disposal scenario, an average transportation distance of 20 km to the nearest station is assumed. Transport over this short distance is, analogue to module A2, modelled with freight lorries with a capacity of 16-32 metric ton, EURO6 in a European setting (RER).

The GWP-biogenic results over all modules have to equal zero, as no credits due to delayed emissions or permanent storage of biogenic carbon in the landfilled product are allowed in consideration of the product's life cycle. A virtual emission of biogenic CO₂ is therefore applied in C4, equalling the product's inherent storage of biogenic carbon from modules A1-A3.

D Benefits and loads beyond the system boundary

This stage of the LCA assesses the reuse, recovery and recycling potential of the product. While it is theoretically possible to decompose AURO wall paints, it is, at this point in time, highly impractical, uneconomic and unusual to separate them from their substrate for a dedicated recycling effort to achieve a full cradle-to-cradle life cycle. Due to these practical reasons, no such potential is declared for the discussed product.

Modules declared, geographical scope, share of specific data (in GWP-GHG results) and data variation (in GWP-GHG results):

	Product stage			Construction process stage		Use stage							End of life stage				Resource recovery stage
	Raw material supply	Transport	Manufacturing	Transport	Construction installation	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
Module	A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Modules declared	X	X	X	ND	ND	ND	ND	ND	ND	ND	ND	ND	X	X	X	X	X
Geography	GLO	GLO	GER	ND	ND	ND	ND	ND	ND	ND	ND	ND	RER	RER	RER	RER	-
Specific data used	> 90%			-	-	-	-	-	-	-	-	-	-	-	-	-	-
Variation – products	< 10% for each product group			-	-	-	-	-	-	-	-	-	-	-	-	-	-
Variation – sites	Manufactured in one site			-	-	-	-	-	-	-	-	-	-	-	-	-	-

Grip Coat, granulated No. 506:



Technical Data

Property	Value
Medium grain	<0.2 mm
Density	1.57 kg/L
sd-value	<0.01 m

1. SUBSTRATES

1.1 Suitable substrates

Mineral substrates, plaster, clay, concrete, lime-sand bricks, brickwork, gypsum plasterboard, cement fibre boards, damp room boards, woodchip, vinyl wallpaper, glass fibre fabrics, adhesive and wettable old coatings; interior latex paints or lacquer coats after a positive compatibility test.

1.2 General substrate requirements

Substrate must be dry, clean, solid, even, chemically neutral to moderately alkaline, free of oil and grease, adhesive, without bleeding substances, durably able to support.

2. COATING SYSTEM

2.1 Substrate preparation

Remove, brush off, repair brittle surface parts. Remove chalky, crumbling substances by brushing and solidify with AURO Plaster primer No. 301, if necessary. Remove sintered skin by sanding down, parting agents by washing. Fill surface defects, holes, cracks with AURO High-grade wall filler No. 338 and sand down burrs. Glue loose wallpaper seams, remove adhesive residues. Remove badly adhering, non-adhesive, non-wettable or otherwise unsuitable old coatings entirely.

2.2 Basic treatment

Treat surfaces once (interior) or twice (exterior) with AURO Grip coat, fine No. 505 or Grip coat, granulated No. 506. Strongly absorptive substrates should be treated twice in any case. It is imperative to make pre-tests on bleeding substances, e.g. on fibreboards. Where a subsequent coloured treatment is intended, it is recommended to already tint the primer with up to 10% of AURO Full-shade tinting colour No. 330.

Content information

Product components	Weight, kg / kg	Post-consumer material, weight-%
REPLEBIN® (Binder)	11	0
Water	32	0
Fillers	55	0
Titanium dioxide	0	0
Additives	2	0
TOTAL	100	0
Packaging materials	Weight, kg / kg	Weight-% (versus the product)
Post-consumer polypropylene (bucket and handle)	2.98E-03	2.33%
Virgin polypropylene (bucket lid, Bag-in-Box IBC shell)	8.68E-04	0.68%
Polyethylene (IBC-Inliner)	0	0.00%
Steel (bucket, lid and handle)	0	0.00%
Paper labels	5.51E-05	0.04%
Corrugated paperboard (transport protection)	5.48E-04	0.43%
Adhesive tape (transport protection)	2.96E-06	0.00%
Polypropylene (strapping tape, transport protection)	2.17E-05	0.02%
TOTAL	4.47E-03	3.51%

2.3 Intermediate treatment

Walls treated with AURO Grip coats No. 506 can be coated with all AURO emulsion or lime paints and plasters.

3. AFTER-TREATMENT

Can be overcoated with all AURO emulsion or lime paints and plasters.

4. REMARKS

- Check substrates for suitability and compatibility before use.
- Avoid exposure to direct sunlight, humidity and dirt during the application and the drying process.
- Application temperature: 10 °C min., 35 °C max., 85% rel. air humidity max., ideally 20-23 °C, 40-65% relative air humidity.
- The Grip coats tend to settle, especially when it is diluted, therefore stir well before use and repeatedly during application.
- Protect surfaces not to be coated and environment from product splashes.
- Remove stains and splashes immediately with water, if necessary, add AURO Plant soap No. 411.
- Leave new plaster and sand-lime brickwork uncoated for at least 6 weeks.
- Check and maintain surfaces regularly, repair defects immediately to ensure optimum, durable protection of the surfaces.
- With regard to exterior coatings, please note that the AURO Grip coat No. 506 contains no fungicides or algicides. A follow-up treatment with a house paint is recommended.
- The respective and general state-of-the-art practices must be observed (e.g. BFS (Federal Committee for Paints and the Protection of Property) Information Sheets, VOB (Contract Procedure for Construction Work), etc.).
- All coating work must be adapted to the object to be coated and its intended use.

Disclaimer: For other AURO products mentioned here, see the respective Technical Data Sheets.

Results of the environmental performance indicators

Disclaimer: The results of modules A1-A3 should not be used without consideration of the results of module C. The estimated impact results are only relative statements which do not indicate the end points of the impact categories, exceeding threshold values, safety margins and/or risks.

Mandatory impact category indicators according to EN 15804

Results per functional or declared unit																
Indicator	Unit	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
GWP-fossil	kg CO ₂ eq.	8.32E-02	ND	ND	ND	ND	ND	ND	ND	ND	ND	0	2.91E-04	0	7.25E-03	0
GWP-biogenic	kg CO ₂ eq.	-1.39E-02	ND	ND	ND	ND	ND	ND	ND	ND	ND	0	2.01E-07	0	1.39E-02	0
GWP-luluc	kg CO ₂ eq.	3.09E-03	ND	ND	ND	ND	ND	ND	ND	ND	ND	0	9.65E-08	0	4.46E-07	0
GWP-total	kg CO ₂ eq.	7.59E-02	ND	ND	ND	ND	ND	ND	ND	ND	ND	0	2.91E-04	0	2.12E-02	0
ODP	kg CFC 11 eq.	7.66E-09	ND	ND	ND	ND	ND	ND	ND	ND	ND	0	5.78E-12	0	2.46E-11	0
AP	mol H ⁺ eq.	5.70E-04	ND	ND	ND	ND	ND	ND	ND	ND	ND	0	6.06E-07	0	5.73E-06	0
EP-freshwater	kg P eq.	1.92E-05	ND	ND	ND	ND	ND	ND	ND	ND	ND	0	1.97E-08	0	8.08E-08	0
EP-marine	kg N eq.	2.09E-04	ND	ND	ND	ND	ND	ND	ND	ND	ND	0	1.46E-07	0	2.22E-06	0
EP-terrestrial	mol N eq.	1.10E-03	ND	ND	ND	ND	ND	ND	ND	ND	ND	0	1.57E-06	0	2.41E-05	0
POCP	kg NMVOC eq.	3.48E-04	ND	ND	ND	ND	ND	ND	ND	ND	ND	0	1.01E-06	0	1.03E-05	0
ADP-minerals&metals*	kg Sb eq.	1.25E-06	ND	ND	ND	ND	ND	ND	ND	ND	ND	0	9.69E-10	0	1.74E-09	0
ADP-fossil*	MJ	2.72E+01	ND	ND	ND	ND	ND	ND	ND	ND	ND	0	4.09E-03	0	1.87E-02	0
WDP*	m ³	1.52E-01	ND	ND	ND	ND	ND	ND	ND	ND	ND	0	2.00E-05	0	8.58E-05	0
Acronyms	GWP-fossil = Global Warming Potential fossil fuels; GWP-biogenic = Global Warming Potential biogenic; GWP-luluc = Global Warming Potential land use and land use change; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential, Accumulated Exceedance; EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment; EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment; EP-terrestrial = Eutrophication potential, Accumulated Exceedance; POCP = Formation potential of tropospheric ozone; ADP-minerals&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Abiotic depletion for fossil resources potential; WDP = Water (user) deprivation potential, deprivation-weighted water consumption															

* Disclaimer: The results of this environmental impact indicator shall be used with care as the uncertainties of these results are high or as there is limited experience with the indicator.

Additional mandatory and voluntary impact category indicators

Results per functional or declared unit																
Indicator	Unit	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
GWP-GHG ¹	kg CO ₂ eq.	9.11E-02	ND	ND	ND	ND	ND	ND	ND	ND	ND	0	2.91E-04	0	7.26E-03	0

Resource use indicators

Results per functional or declared unit																
Indicator	Unit	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
PERE	MJ	1.31E+00	ND	ND	ND	ND	ND	ND	ND	ND	ND	0	6.17E-05	0	2.57E-04	0
PERM	MJ	1.03E+02	ND	ND	ND	ND	ND	ND	ND	ND	ND	0	8.49E-06	0	3.59E-05	0
PERT	MJ	1.04E+02	ND	ND	ND	ND	ND	ND	ND	ND	ND	0	7.02E-05	0	2.93E-04	0
PENRE	MJ	2.94E+01	ND	ND	ND	ND	ND	ND	ND	ND	ND	0	3.71E-03	0	1.70E-02	0
PENRM	MJ	7.08E+01	ND	ND	ND	ND	ND	ND	ND	ND	ND	0	3.80E-04	0	1.74E-03	0
PENRT	MJ	1.00E+02	ND	ND	ND	ND	ND	ND	ND	ND	ND	0	4.09E-03	0	1.87E-02	0
SM	kg	1.79E-02	ND	ND	ND	ND	ND	ND	ND	ND	ND	0	4.68E-06	0	1.76E-05	0
RSF	MJ	1.11E-01	ND	ND	ND	ND	ND	ND	ND	ND	ND	0	1.31E-06	0	4.98E-06	0
NRSF	MJ	0	ND	ND	ND	ND	ND	ND	ND	ND	ND	0	0	0	0	0
FW	m ³	4.74E-03	ND	ND	ND	ND	ND	ND	ND	ND	ND	0	5.50E-07	0	-1.76E-04	0
Acronyms	PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy re-sources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water															

¹ This indicator accounts for all greenhouse gases except biogenic carbon dioxide uptake and emissions and biogenic carbon stored in the product. As such, the indicator is identical to GWP-total except that the CF for biogenic CO₂ is set to zero.

Waste indicators

Results per functional or declared unit																
Indicator	Unit	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Hazardous waste disposed	kg	5.20E-03	ND	ND	ND	ND	ND	ND	ND	ND	ND	0	4.06E-06	0	1.97E-05	0
Non-hazardous waste disposed	kg	1.23E-01	ND	ND	ND	ND	ND	ND	ND	ND	ND	0	4.50E-05	0	2.72E-01	0
Radioactive waste disposed	kg	1.04E-06	ND	ND	ND	ND	ND	ND	ND	ND	ND	0	1.32E-09	0	5.73E-09	0

Output flow indicators

Results per functional or declared unit																
Indicator	Unit	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Components for re-use	kg	0	ND	ND	ND	ND	ND	ND	ND	ND	ND	0	0	0	0	0
Material for recycling	kg	1.19E-02	ND	ND	ND	ND	ND	ND	ND	ND	ND	0	4.24E-06	0	1.38E-05	0
Materials for energy recovery	kg	4.75E-07	ND	ND	ND	ND	ND	ND	ND	ND	ND	0	5.87E-10	0	2.24E-09	0
Exported energy, electricity	MJ	2.05E-03	ND	ND	ND	ND	ND	ND	ND	ND	ND	0	6.95E-07	0	2.88E-06	0
Exported energy, thermal	MJ	4.61E-03	ND	ND	ND	ND	ND	ND	ND	ND	ND	0	9.84E-07	0	1.59E-05	0

LCA result interpretation

In most categories, 90% to 99% of the total impact declared stems from the sum of modules A1-A3. The exception is the non-hazardous waste disposed, where the final disposal in module C4 contributes as approximately two thirds of the total impact. Especially for the non-GWP indicators barring the stated exception, the impact from the end-of-life stage is almost negligible.

Additional environmental, social and economic information

For further information, please take a look at our [latest sustainability report](#) (German only).

References

General Programme Instructions of the International EPD® System. Version 4.0.

PCR 2019:14. Construction Products. Version 1.3.4

Candidate List of substances of very high concern for Authorisation (SVHC) published in accordance with Article 59 (10) of the REACH Regulation.
(<https://echa.europa.eu/candidate-list-table>)

UN CPC, Version 1.1 – Code 3511 Paints and varnishes and related products.
(<https://unstats.un.org/unsd/classifications/Econ/Detail/EN/16/3511>)

Scholt Energy Energy Label 2023, Green Electricity 'Garantiert Grün'.
(<https://www.scholt.de/media/s33eqbss/sec-stomkennzeichnung-2023-de-en.pdf>)

AURO Sustainability Report 2023.
(https://auro.hosting-kitchen.de/wp-content/uploads/2024/01/AURO-Nachhaltigkeitsbericht-2023_01.2024.pdf)

